



STRETCH FILM Anti Corrosion Stretch LDPE Film

VCI2000 Stretch film is a polythylene film impregnated with our high-tech eco-firendly volatile corrosion inhibitors (VCIs). It is designed to MULTI-METALS protection (ferrous and nonferrous metals) from corrosion/oxidation during storage and transport when stored in covered place or packed in boxes, cartons, containers etc.



- Dry protection No need to apply or remove
 Protective Liquids
- Does Not Effect on the Metal Surface Properties
- Manual or Automatic Use
- Safe and Friendly TRGS 615 Approved -Recyclable as Polyethylene in According with 94/62 EC Regulation

AVAILABILITY

23 - 28µm ± 2

500mm

3kg ± 5%

77mm

PRODUCT PROPERTIES						
Film Estensibile LDPE + VCI2000						
DENSITY 0,918 - 0,920 g/cm ³						
TEAR STRENGTH	MD 30 N/mm ²					
	TD 18 N/mm ²					
ELONGATION	MD 380%					
	TD 650%					
YIELD STRENGTH	MD 9 N/mm ²					
	TD 8 N/mm ²					
RECYCLABILITY	94/62 EC Regulation					
STORAGE	< 50°C - (122°F)					
	24 months into original					
	package					

The above process parameters are based on testing done on sample of $_{23}\mu m$ in according with test method ASTM D 882 and PLT o1

For	effective	protection	from	corrosion	is	strongly		
recommended its use in indoor storage environments or with								
external containers such as boxes, cartons or wooden crates								

The information contained herein is based on available data from reliable sources and is accurate to the best of LOGIN EUROPE's knowledge at the time of this publication. The user is solely responsible for determining the suitability and completeness of such information for their particular application and for adopting appropriate safety precautions. This data is not to be taken as a warranty or representation for which LOGIN EUROPE Srl assumes legal or financial responsibility. 16092016

COPYRIGHT © LOGIN EUROPE SRL 2016. ALL RIGHTS RESERVED.

loq	ine	uro	pe.	e u

THICKNESS

ROLL WEIGHT

INNER CORE DIAMETER

WIDTH

info@logineurope.eu