



DATA SHEET

Stretch Film Anti Corrosion Stretch LDPE Film

VCI 2000 Stretch film is a polythylene film impregnated with our high-tech eco-firendly volatile corrosion inhibitors (VCIs). It is designed to MULTI-METALS protection (ferrous and non-ferrous metals) from corrosion/oxidation during storage and transport when stored in covered place or packed in boxes, cartons, containers etc.



- Dry protection No need to apply or remove protective Liquids
- Does Not Effect on the Metal Surface Properties
- Manual or Automatic Use
- Safe and Friendly TRGS 615 Approved
- Recyclable as Polyethylene in According with 94/62 & 129/97 CE Regulations

PRODUCT PROPERTIES	
LDPE Stretch Film + VCI	
DENSITY	0,918 - 0,920 g/cm³
TEAR STRENGTH	MD 30 N/mm² TD 18 N/mm²
ELONGATION	MD 380% TD 650%
YIELD STRENGTH	MD 9 N/mm² TD 8 N/mm²
CORROSION TEST	TL 8135-0043
RECYCLABILITY	94/62 & 129/97 CE Regulation
STORAGE	< 122°F - (50°C) 24 months into original

24 months into original package

The above process parameters are based on testing done on sample of 23µm in according with test method ASTM D 882 and PLT 01

For effective protection from corrosion is strongly recommended its use in indoor storage environments or with external containers such as boxes, cartons or wooden crates

AVAILABILITY

- Thickness: 23 28µm ± 2
- Width: 500mm
- Roll Weight: 3kg ± 5%
- Inner Core Diameter: 77mm

The information contained herein is based on available data from reliable sources and is accurate to the best of LOGIN EUROPE's knowledge at the time of this publication. The user is solely responsible for determining the suitability and completeness of such information for their particular application and for adopting appropriate safety precautions. This data is not to be taken as a warranty or representation for which LOGIN EUROPE Srl assumes legal or financial responsibility. 05022021

COPYRIGHT © LOGIN EUROPE SRL 2018. ALL RIGHTS RESERVED.